

SAFETY DATA SHEET

Tradeweld Black Part A

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Tradeweld Black Part A

Container size 400ml,50ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier Trade Grade Products Ltd
10 Victory Close
Woolsbridge Industrial Park
Wimborne
Dorset
BH21 6SX
+44 (0)1202 820177
+44 (0)1202 814011
sales@thegluepeople.co.uk

1.4. Emergency telephone number

Emergency telephone +44 (0)1202 820177

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Corr. 1A - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H225 Highly flammable liquid and vapour.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H412 Harmful to aquatic life with long lasting effects.

Tradeweld Black Part A

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P240 Ground/bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P260 Do not breathe vapour/spray.</p> <p>P261 Avoid breathing vapour/spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P310 Immediately call a POISON CENTER/doctor.</p> <p>P312 Call a POISON CENTER/doctor if you feel unwell.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P363 Wash contaminated clothing before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p>
---------------------------------	---

Contains methyl methacrylate, methacrylic acid, maleic acid

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

methyl methacrylate	30-60%
CAS number: 80-62-6	EC number: 201-297-1
Classification	
Flam. Liq. 2 - H225	
STOT SE 3 - H335	
Skin Sens. 1 - H317	
Skin Irrit. 2 - H315	

Tradeweld Black Part A

methacrylic acid	5-10%
CAS number: 79-41-4	EC number: 201-204-4
Classification	
Acute Tox. 4 - H312	
Acute Tox. 4 - H302	
Skin Corr. 1A - H314	
STOT SE 3 - H335	
STOT SE 3 - H335	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
maleic acid	1-5%
CAS number: 110-16-7	EC number: 203-742-5
Classification	
Eye Irrit. 2 - H319	
STOT SE 3 - H335	
Acute Tox. 4 - H302	
Skin Sens. 1 - H317	
Skin Irrit. 2 - H315	
STOT SE 3 - H335	
STOT SE 3 - H335	
2,6-Di-Tert-Butyl-P-Cresol (BHT)	<1%
CAS number: 128-37-0	
M factor (Acute) = 1	M factor (Chronic) = 1
Classification	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
α,α-dimethylbenzyl hydroperoxide	<1%
CAS number: 80-15-9	EC number: 201-254-7
Classification	
Org. Perox. E - H242	
STOT SE 3 - H335	
Acute Tox. 3 - H331	
Acute Tox. 4 - H312	
Skin Corr. 1B - H314	
STOT RE 2 - H373	
Acute Tox. 4 - H302	
STOT SE 3 - H335	
Eye Dam. 1 - H318	
STOT SE 3 - H335	
Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

Tradeweld Black Part A

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
Ingestion	Do not induce vomiting. Give plenty of water to drink. Get medical attention. Never give anything by mouth to an unconscious person.
Skin contact	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if symptoms are severe or persist after washing. Use appropriate hand lotion to prevent defatting and cracking of skin.
Eye contact	Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Skin contact	Burns can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Toxic gases or vapours.
-------------------------	-------------------------

5.3. Advice for firefighters

Protective actions during firefighting	Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. Do not use water jet as an extinguisher, as this will spread the fire. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet.
-----------------------------	---

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Tradeweld Black Part A

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Eliminate all sources of ignition.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Mechanical ventilation or local exhaust ventilation may be required. Avoid contact with skin and eyes. Take precautionary measures against static discharges. Ground/bond container and receiving equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene When using do not eat, drink or smoke.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

methyl methacrylate

Long-term exposure limit (8-hour TWA): WEL 50 ppm 208 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 416 mg/m³

2,6-Di-Tert-Butyl-P-Cresol (BHT)

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Rubber (natural, latex). Neoprene. Nitrile rubber.

Other skin and body protection

Wear apron or protective clothing in case of contact.

Hygiene measures

Provide eyewash station. Do not eat, drink or smoke when using this product. Good personal hygiene procedures should be implemented. Wash promptly with soap and water if skin becomes contaminated.

Tradeweld Black Part A

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Paste.
Colour	White/off-white.
Odour	Acrylic
Odour threshold	No information available.
pH	Not available.
Melting point	No information available.
Initial boiling point and range	Not available.
Flash point	11°C TCC (Tag closed cup).
Evaporation rate	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Solubility(ies)	Insoluble in water.
Partition coefficient	No information available.
Auto-ignition temperature	No information available.
Decomposition Temperature	No information available.
Oxidising properties	Not available.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity See Section 10.3 (Possibility of hazardous reactions) for further information.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. May polymerise.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions May polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid exposure to high temperatures or direct sunlight.

10.5. Incompatible materials

Materials to avoid Avoid contact with the following materials: Alkali metals. Strong oxidising agents. Strong acids. Strong alkalis. Organic peroxides/hydroperoxides. Inorganic peroxides.

10.6. Hazardous decomposition products

Tradeweld Black Part A

Hazardous decomposition products Oxides of: Carbon. Other toxic gases and vapours

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 6,250.0

Acute toxicity - dermal

ATE dermal (mg/kg) 15,714.29

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 600.0

Inhalation	Irritation of nose, throat and airway. May cause damage to mucous membranes in nose, throat, lungs and bronchial system.
Ingestion	Causes burns. May cause chemical burns in mouth, oesophagus and stomach. May cause stomach pain or vomiting.
Skin contact	Causes burns. May cause skin sensitisation or allergic reactions in sensitive individuals.
Eye contact	Causes burns. Irritation of eyes and mucous membranes. Severe irritation, burning and tearing.

SECTION 12: Ecological Information

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential Potentially bioaccumulating.

Partition coefficient No information available.

12.4. Mobility in soil

Mobility Not available

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

Tradeweld Black Part A

14.1. UN number

UN No. (ADR/RID)	2924
UN No. (IMDG)	2924
UN No. (ICAO)	2924
UN No. (ADN)	2924


14.2. UN proper shipping name

Proper shipping name (ADR/RID)	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper shipping name (IMDG)	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper shipping name (ICAO)	FLAMMABLE LIQUID, CORROSIVE, N.O.S.
Proper shipping name (ADN)	FLAMMABLE LIQUID, CORROSIVE, N.O.S.

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID subsidiary risk	8
ADR/RID classification code	FC
ADR/RID label	3
IMDG class	3
IMDG subsidiary risk	8
ICAO class/division	3
ICAO subsidiary risk	8
ADN class	3
ADN subsidiary risk	8

Transport labels



14.4. Packing group

ADR/RID packing group	II
IMDG packing group	II
ADN packing group	II
ICAO packing group	II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-C

Tradeweld Black Part A

ADR transport category	2
Emergency Action Code	•3WE
Hazard Identification Number (ADR/RID)	338
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Dangerous Preparations Directive 1999/45/EC. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
-----------------------	--

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	09/07/2015
SDS number	5081
Hazard statements in full	H225 Highly flammable liquid and vapour. H242 Heating may cause a fire. H302 Harmful if swallowed. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H331 Toxic if inhaled. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

Tradeweld Black Part A

PRECAUTIONS: This product and the auxiliary materials normally combined with it are capable of producing adverse health effects ranging from minor skin irritation to serious systemic effects. None of these materials should be used, stored, or transported until the handling precautions and recommendations as stated in the Material Safety Data Sheets (MSDS) for this and all other products being used are understood by all persons who will work with the product.

WARRANTY: All products purchased from or supplied by TGP Ltd are subject to terms and conditions set out in the contract. TGP warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by TGP is considered accurate but are furnished upon the express condition the customer shall make its own assessment to determine the product's suitability for a particular purpose. TGP makes no other warranty, either express or implied, including those regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose; or that the use of such other information or product will not infringe any patent.