



The Glue People

Trade Grade Products Ltd
10 Victory Close
Woolbridge Industrial Park
Three Legged Cross
Wimborne, Dorset, BH21 6SX

Tel 01202 820177
Fax 01202 814011

BANNER TAPE

Double Sided Polyester Film Tape.

TECHNICAL INFORMATION

Thickness, Adhesive + Carrier	0.215 mm	
Adhesive	High performance solvent acrylic	
Carrier material	Polyester film	
Carrier thickness	0.025 mm	
Release liner	Red MOPP film	
Liner thickness	0.07 mm	
180° Peel adhesion	Immediate	1400 N/mm
	After 24 hours	1920 N/mm
Tack *	640 N/mm	
Liner release	10 N/mm	
Service temperature	-20°C to +120°C	
Short term performance	170°C < 1 hour	
Application temperature	+5°C to +25°C	
Dynamic Shear **	Immediate	135 N/625 mm ²
	After 24 hours	156 N/625 mm ²
Static Shear 2Kg @ 23°C 625mm²	85 Hours	
High Temp Shear 0.5Kg @ 70°C 625mm²	100 Hours	
Shelf Life	12 months	
Test Methods	* AFERA 4015	** ASTM D-1002

GENERAL INFORMATION

Data Ranges

The data contained herein may be reported as a typical value and/or range. Values are based on actual test data and are verified on a periodic basis.

Important Notice

Data contained in this document is for information only and is believed to be reliable. Trade Grade Products Ltd (TGP) cannot assume responsibility for results obtained by others over whose methods we have no control.

It is the user's responsibility to determine suitability of the product for any specific purpose and TGP is pleased to provide a sample upon request.